

Package ‘dendRoAnalyst’

July 3, 2020

Type Package

Date 2020-07-03

Title A Tool for Processing and Analyzing Dendrometer Data

Version 0.1.1

Maintainer Sugam Aryal <sugam.aryal@fau.de>

Description There are various functions for managing and cleaning data before the application of different approaches. This includes identifying and erasing sudden jumps in dendrometer data not related to environmental change, identifying the time gaps of recordings, and changing the temporal resolution of data to different frequencies. Furthermore, the package calculates daily statistics of dendrometer data, including the daily amplitude of tree growth. Various approaches can be applied to separate radial growth from daily cyclic shrinkage and expansion due to uptake and loss of stem water. In addition, it identifies periods of consecutive days with user-defined climatic conditions in daily meteorological data, then check what trees are doing during that period.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Depends R (>= 2.10), boot, pspline, zoo, graphics, grDevices, stats,
base

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Sugam Aryal [aut, cre, dtc],
Martin Häusser [aut],
Jussi Grießinger [aut],
Ze-Xin Fan [aut],
Achim Bräuning [aut, dgs]

Repository CRAN

Date/Publication 2020-07-03 19:00:07 UTC

R topics documented:

clim.twd	2
daily.data	3
dendro.resample	4
dendro.truncate	5
gf_nepa17	6
jump.locator	6
ktm_rain17	7
nepa	8
nepa17	8
nepa2	9
network.interpolation	9
phase.sc	10
phase.zg	12
spline.interpolation	14
twd.maxima	15
Index	16

clim.twd	<i>Calculating relative growth change during no-rain periods.</i>
----------	---

Description

This function calculates the number and the location of climatically adverse periods within a climate time series. The user can define a duration and threshold of these conditions. The function also provides the relative radial/circumferencial change during each adverse period for the original or normalized data. See [Raffelsbauer et al., \(2019\)](#) for more details.

Usage

```
clim.twd(
  df,
  Clim,
  dailyValue = "max",
  thresholdClim = 0,
  thresholdDays = 2,
  norm = F,
  showPlot
)
```

Arguments

df	dataframe with first column containing date and time in the format yyyy-mm-dd HH:MM:SS and the dendrometer data in following columns.
Clim	dataframe with the first column containing doy and second column containing corresponding climate data.

dailyValue	either 'max', 'min', or 'mean' for selecting the daily resampled value. Default is 'max'. See dendro.resample for details.
thresholdClim	numeric, the threshold for the respective climatic parameter. E.g. if climatic data is precipitation then days, where precipitation is below or equal to this value, are considered as adverse climate. Default is 0.
thresholdDays	numeric, the minimum number of consecutive adverse days to be considered for analysis. For example, thresholdDays=2 means the relative radial/circumferential change is calculated for adverse periods lasting for more than 2 days. Default is 2.
norm	logical, if TRUE the function uses normalized data instead of original dataset. Default is FALSE.
showPlot	logical, if TRUE, generates plots.

Value

A dataframe containing the respective periods, relative radial/circumference change for each tree, the ID for each period and their beginning and end.

References

Raffelsbauer V, Spann S, Peña K, Pucha-Cofrep D, Steppe K, Bräuning A (2019) Tree Circumference Changes and Species-Specific Growth Recovery After Extreme Dry Events in a Montane Rainforest in Southern Ecuador. *Front Plant Sci* 10:342. <https://doi.org/10.3389/fpls.2019.00342>

Examples

```
library(dendRoAnalyst)
data(gf_nepa17)
data(ktm_rain17)
relative_dry_growth<-clim.twd(df=gf_nepa17, Clim=ktm_rain17, dailyValue='max', showPlot=TRUE)
1

head(relative_dry_growth,10)
```

daily.data

Calculation of daily statistics for dendrometer data

Description

This function calculates various statistics of dendrometer data on a daily basis. The daily statistics includes the daily maximum and minimum with their corresponding times and daily amplitude (difference between daily maximum and minimum). See [King et al. \(2013\)](#) for details.

Usage

```
daily.data(df, TreeNum)
```

Arguments

df	dataframe with first column containing date and time in the format yyyy-mm-dd HH:MM:SS and the dendrometer data in following columns.
TreeNum	numerical value indicating the tree to be analysed. E.g. '1' refers to the first dendrometer data column in <i>df</i> .

Value

A dataframe with the daily statistics of the dendrometer data that contains:

Columns	Description
DOY	The day of year.
min	The minimum value record for the corresponding day.
Time_min	The time when minimum value recorded for the corresponding day.
max	The maximum value record for the corresponding day.
Time_max	The time when maximum value recorded for the corresponding day.
mean	The daily average value of the dendrometer reading.
median	The daily median value of the dendrometer reading.
amplitude	The difference between daily maximum and daily minimum.

References

King G, Fonti P, Nievergelt D, Büntgen U, Frank D (2013) Climatic drivers of hourly to yearly tree radius variations along a 6°C natural warming gradient. *Agricultural and Forest Meteorology* 168:36–46. <https://doi.org/10.1016/j.agrformet.2012.08.002>

Examples

```
library(dendRoAnalyst)
data(nepa17)
daily_stats<-daily.data(df=nepa17, TreeNum=1)
head(daily_stats,10)
```

dendro.resample

Resampling temporal resolution of dendrometer data

Description

This function is designed to change the temporal resolution of data. Depending on the objective, the user can define either maximum, minimum, or mean values to resample data in hourly, daily, weekly or monthly frequency.

Usage

```
dendro.resample(df, by, value)
```

Arguments

df	dataframe with first column containing date and time in the format yyyy-mm-dd HH:MM:SS.
by	either <i>H</i> , <i>D</i> , <i>W</i> or <i>M</i> to resample data into hourly, daily, weekly or monthly resolution.
value	either <i>max</i> , <i>min</i> or <i>mean</i> for the resampling value.

Value

Dataframe with resampled data.

Examples

```
library(dendRoAnalyst)
data(nepa17)
# To resample monthly with maximum value
resample_M<-dendro.resample(df=nepa17[,1:2], by='M', value='max')
head(resample_M,10)
```

dendro.truncate *Truncation of the dendrometer data*

Description

This function is helpful to truncate dendrometer data for a user-defined period.

Usage

```
dendro.truncate(df, CalYear, DOY)
```

Arguments

df	dataframe with the first column named date and time in the format yyyy-mm-dd HH:MM:SS.
CalYear	numerical value or array of two elements for the desired year of calculation.
DOY	numerical value or array of two elements representing the day of year. If we provide an array instead of a single value for CalYear and a single value for DOY, it truncates data from the DOY of the first CalYear to the same DOY of the second CalYear. Conversely, if we provide one value for CalYear and an array of two elements for DOY truncates the data form first DOY to second DOY within the same CalYear. Finally, if we provide an array with two values for both DOY and CalYear, it truncates data from the first DOY of the first CalYear to the second DOY of second CalYear.

Value

A dataframe with the truncated data for the defined periods.

Examples

```
library(dendRoAnalyst)
data(nepa)
#Extracting data from doy 20 to 50 in 2017.
trunc1<-dendro.truncate(df=nepa, CalYear=2017, DOY=c(20,50))
head(trunc1,10)
```

gf_nepa17

Dendrometer data of Kathmandu for 2017 with gap filled

Description

The dendrometer data from three Chir pine tree collected in hourly resolution for 2017.

Usage

```
gf_nepa17
```

Format

A data frame with 8760 rows and 3 variables:

Time datetime time of data recording

T2 double reading for first tree

T3 double reading for second tree

jump.locator

Removing artefacts due to manual adjustments of dendrometers

Description

Dendrometers generally have limited memory capacity beyond which it stops recording. To keep the measurement ongoing, they should be adjusted periodically, which can cause positive or negative jumps in the data. This function locates these artefacts and interactively adjusts them one by one.

Usage

```
jump.locator(df, TreeNum, v)
```

Arguments

df	dataframe with first column containing date and time in the format yyyy-mm-dd HH:MM:SS and the dendrometer data in following columns.
TreeNum	numerical value indicating the tree to be analysed. E.g. '1' refers to the first dendrometer data column in <i>df</i> .
v	numerical value which is considered as artefact. E.g. v=1 implies that if the difference to the consecutive data point is more than 1 or less than -1, it will be considered as an artefact.

Value

A dataframe containing jump-free dendrometer data.

Examples

```
library(dendRoAnalyst)
data(nepa)
jump_free_nepa<-jump.locator(df=nepa, TreeNum=1 ,v=1)
head(jump_free_nepa,10)
```

ktm_rain17

Daily rainfall data of Kathmandu for 2017.

Description

This file contains daily rainfall data of Kathmandu. The source of this data is 'Government of Nepal, Department of Hydrology and Meteorology'.

Usage

```
ktm_rain17
```

Format

A data frame with 365 rows and 2 variables:

DOY double Day of year.

rainfall double rainfall in millimeters

Source

<http://www.mfd.gov.np/city?id=31/>

nepa

Dendrometer data from Kathmandu

Description

Dendrometer data from three Chir pine trees collected in hourly resolution for 2 years.

Usage

nepa

Format

A data frame with 14534 rows and 3 variables:

Time datetime time of data recording

T2 double reading for first tree

T3 double reading for second tree

nepa17

Dendrometer data of Kathmandu for 2017

Description

Dendrometer data from three Chir pine tree collected in hourly resolution for 2017.

Usage

nepa17

Format

A data frame with 8753 rows and 3 variables:

Time datetime time of data recording

T2 double reading for first tree

T3 double reading for second tree

 nepa2

Dendrometer data from Kathmandu version 2

Description

Dendrometer data from three Chir pine trees collected in hourly resolution for 2 years with separated time.

Usage

nepa2

Format

A data frame with 14534 rows and 8 variables:

year numeric year of data recording
 month numeric months of data recording
 day numeric days of data recording
 hours numeric hours of data recording
 minutes numeric minutes of data recording
 seconds numeric seconds of data recording
 T2 double reading for first tree
 T3 double reading for second tree

 network.interpolation *Interpolation of NA values using the dendrometer network*

Description

A function to interpolate the missing data of a dendrometer with the help of other dendrometers from the same site, provided they have the same measurement period and temporal resolution.

Usage

network.interpolation(df, referenceDF, niMethod)

Arguments

df	dataframe with first column containing date and time in the format yyyy-mm-dd HH:MM:SS and dendrometer data in the second column and onward. The data gaps must be filled with NA using the gap.interpolation function.
referenceDF	dataframe with other dendrometers to be used as reference for the interpolation. The more dendrometers are included, the more robust will be the interpolation.
niMethod	string, either <i>'linear'</i> or <i>'proportional'</i> for interpolation method.

Value

A dataframe with NA values replaced by interpolated data.

Examples

```
library(dendRoAnalyst)
data("gf_nepa17")
df1<-gf_nepa17
# Creating an artificial reference dataset.
df2<-cbind(gf_nepa17,gf_nepa17[,2:3],gf_nepa17[,2:3])
# Creating gaps in dataset by replacing some of the reading with NA in dataset.
df1[40:50,3]<-NA
# Using proportional interpolation method.
df1_NI<-network.interpolation(df=df1, referenceDF=df2, niMethod='proportional')
head(df1_NI,10)
```

phase.sc

Application of the stem-cycle approach to calculate different phases, their duration and to plot them.

Description

This function analyses the dendrometer data using Stem-cycle approach ([Downs et al. 1999](#); [Deslauriers et al. 2011](#)). A function that defines three phases: 1) Shrinkage, when the dendrometer reading is less than previous reading, 2) Expansion, when current reading is more than previous reading and 3) Increment, when current reading is higher than the previous maximum. Additionally, it calculates various statistics for each phase.

Usage

```
phase.sc(
  df,
  TreeNum,
  smoothing = NULL,
  outputplot = FALSE,
  days,
  cols = c("#fee8c8", "#fdbb84", "#e34a33"),
  phNames = c("Shrinkage", "Expansion", "Increment"),
  cex = NULL,
  cex.axis = NULL,
  cex.legend = NULL,
  font.axis = NULL,
  col.axis = NULL,
  ...
)
```

Arguments

df	dataframe with first column containing date and time in the format yyyy-mm-dd HH:MM:SS. It should contain data with constant temporal resolution for best results.
TreeNum	numerical value indicating the tree to be analysed. E.g. '1' refers to the first dendrometer data column in <i>df</i> .
smoothing	numerical value from 1 to 12 which indicates the length of the smoothing spline, i.e. 1 = 1 hour and 12 = 12 hours. Default is NULL for no smoothing. The function <code>smooth.Pspline</code> is used for smoothing the data.
outputplot	logical, to plot the phase diagram.
days	array with initial and final day for plotting. E.g. $c(a,b)$, where a = initial date and b = final date.
cols	array with three elements representing colors for shrinking, expanding and increasing phases respectively.
phNames	array with three elements for three different phases. Default is " Shrinkage ", " Expansion " and " Increment ".
cex	numeric, for the size of the points. Default is NULL.
cex.axis	numeric, for the size of the axis tick labels. Default is NULL.
cex.legend	numeric, for the size of the legend labels. Default is NULL.
font.axis	numeric, for the font type of the axis tick labels. Default is NULL.
col.axis	color names, for the color of the axis tick labels. Default is NULL.
...	other graphical parameters.

Value

A list of two dataframes. The first dataframe *SC_cycle* with cyclic phases along with various statistics and the second dataframe *SC_phase* with assigned phases for each data point. The dataframe *SC_cycle* contains the beginning, end, duration, magnitude and rate of each phase. The dataframe *SC_phase* contains time and corresponding phases during that time. The contents of *SC_cycle* are:

Columns	Description
Phase	Cyclic phases. 1, 2, and 3 for Shrinkage, Expansion, and Increment respectively.
start	Time when the corresponding phase starts.
end	Time when the corresponding phase ends.
Duration_h	Duration of the corresponding phase in hours.
Duration_m	Duration of the corresponding phase in minutes.
Magnitude	Radial/circumferential change during the corresponding phase in millimeters.
rate	Rate of Radial/circumferential change in micrometers per hour.
DOY	Day of year for the corresponding phase.

References

Deslauriers A, Rossi S, Turcotte A, Morin H, Krause C (2011) A three-step procedure in SAS to analyze the time series from automatic dendrometers. *Dendrochronologia* 29:151–161. <https://doi.org/10.1016/j.dendro.2011.01>

Downes G, Beadle C, Worledge D (1999) Daily stem growth patterns in irrigated Eucalyptus globulus and E. nitens in relation to climate. *Trees* 14:102–111. <https://doi.org/10.1007/PL00009752>

Examples

```
library(dendRoAnalyst)
data(gf_nepa17)
sc.phase<-phase.sc(df=gf_nepa17, TreeNum=1, smoothing=12, outputplot=TRUE, days=c(150,160))
head(sc.phase[[1]],10)
head(sc.phase[[2]],10)
```

phase.zg	<i>Application of the zero-growth approach to calculate different phases, their duration and to plot them.</i>
----------	--

Description

This function analyses data using the zero-growth approach. Initially, it divides the data in two categories: 1) Tree water deficiency (TWD), i.e. the reversible shrinkage and expansion of the tree stem when the current reading is below the previous maximum and, 2) Increment (GRO), the irreversible expansion of the stem when the current reading is above the previous maximum. Then it calculates the TWD for each data point as the difference between the modelled "growth line" and the observed measurement. See [Zweifel et. al.,\(2016\)](#) for details.

Usage

```
phase.zg(
  df,
  TreeNum,
  outputplot,
  days,
  linearCol = "#2c7fb8",
  twdCol = "#636363",
  twdFill = NULL,
  twdFillCol = "#f03b20",
  xlab = "DOY",
  ylab1 = "Stem size variation [mm]",
  ylab2 = "TWD [mm]",
  twdYlim = NULL,
  cex.axis = NULL,
  cex.lab = NULL,
  font.lab = NULL,
  col.lab = NULL,
  font.axis = NULL,
  col.axis = NULL
)
```

Arguments

df	dataframe with first column containing date and time in the format yyyy-mm-dd HH:MM:SS. It should contain data with constant temporal resolution for best results.
TreeNum	numerical value indicating the tree to be analysed. E.g. '1' refers to the first dendrometer data column in <i>df</i> .
outputplot	logical, to plot the phase diagram.
days	array with initial and final day for plotting. E.g. $c(a,b)$, where a = initial date and b = final date.
linearCol	color for the modelled curve.
twdCol	color for the TWD curve.
twdFill	filling method for the area under the TWD curve. Equivalent to density argument of the <code>polygon</code> function in the graphics package of R. Default value is NULL.
twdFillCol	color to fill the area under the TWD curve.
xlab	string, x label of the plot.
ylab1	string, y label of the upper plot.
ylab2	string, y label of the lower plot.
twdYlim	numeric, to define the limit of the y-axis of the lower plot. Default is NULL, which automatically adjusts the y-axis limit.
cex.axis	numeric, for the size of the axis tick labels. Default is NULL.
cex.lab	numeric, for the size of the axis labels. Default is NULL.
font.lab	numeric, for the font type of the axis labels. Default is NULL.
col.lab	color names, for the color of the axis labels. Default is NULL.
font.axis	numeric, for the font type of the axis tick labels. Default is NULL.
col.axis	color names, for the color of the axis tick labels. Default is NULL.

Value

A list of two dataframes. The first dataframe *ZG_cycle* contains the cyclic phases along with various statistics and the second dataframe *ZG_phase* with assigned phases for each data point. The contents of *ZG_cycle* are:

Columns	Description
DOY	Day of year for the corresponding phase.
Phase	TWD for tree water deficit and GRO for irreversible expansion.
start	Time when the corresponding phase starts.
end	Time when the corresponding phase ends.
Duration_h	Duration of the corresponding phase in hours.
Magnitude	Radial/circumferential change in millimeters.
rate	Rate of Radial/circumferential change in micrometers per hour.
Max.twd	Maximum TWD recorded for the corresponding TWD phase.
Max.twd.time	Time of occurrence of maximum TWD value for each TWD phase.
Avg.twd	Average of TWD values for each TWD phase.
STD.twd	Standard deviation of TWD values for each TWD phase.

References

Zweifel R, Haeni M, Buchmann N, Eugster W (2016) Are trees able to grow in periods of stem shrinkage? *New Phytol* 211:839–849. <https://doi.org/10.1111/nph.13995>

Examples

```
library(dendRoAnalyst)
data(gf_nepa17)
zg.phase<-phase.zg(df=gf_nepa17, TreeNum=1, outputplot=TRUE, days=c(150,160))
head(zg.phase[[1]],10)
head(zg.phase[[2]],10)
```

spline.interpolation *Detection and spline interpolation of missing values in dendrometer data.*

Description

This function detects gap(s) in time series, inserts the missing rows based on the provided temporal resolution and assigns NA values to the corresponding value. If required the NA values can be replaced by spline interpolation using [na.spline](#) of the package **zoo**.

Usage

```
spline.interpolation(df, resolution, fill = FALSE)
```

Arguments

df	dataframe with first column containing date and time in the format yyyy-mm-dd HH:MM:SS and following columns with dendrometer data for the same temporal resolution and time period.
resolution	integer, indicating the resolution of dendrometer data in minutes .
fill	logical, if TRUE it fills the NA values using spline interpolation. Default is FALSE.

Value

A dataframe containing the dendrometer data including gaps filled with either NA or interpolated values.

Examples

```
library(dendRoAnalyst)
data(nepa17)
gf_nepa17<-spline.interpolation(df=nepa17, resolution=60)
head(gf_nepa17,10)
```

twd.maxima

*Locating the maxima of TWD periods***Description**

This function detects the TWD phases, including their beginning (TWDb), using the `phase.zg` function. Then it calculates the number, time of occurrence (Tm) and value of every local maximum within each TWD phase. In addition it calculates the time difference between 'TWDb' and each 'Tm' within each TWD phase.

Usage

```
twd.maxima(df, TreeNum, smoothing = 5, showPlot = T, days = c(150, 160), ...)
```

Arguments

<code>df</code>	dataframe with first column containing date and time in the format <code>yyyy-mm-dd HH:MM:SS</code> . It should contain data with constant temporal resolution for best results.
<code>TreeNum</code>	numerical value indicating the tree to be analysed. E.g. '1' refers to the first dendrometer data column in <code>df</code> .
<code>smoothing</code>	numerical value from 1 to 12 which indicates the length of the smoothing spline, i.e. 1 = 1 hour and 12 = 12 hours. Default is 5.
<code>showPlot</code>	logical, if TRUE, it generates a plot. Default is TRUE.
<code>days</code>	array with initial and final day for plotting. E.g. <code>c(a,b)</code> , where a=initial date and b=final date. Default is <code>c(150,160)</code> .
<code>...</code>	additional graphical parameter included in <code>phase.zg</code> .

Value

A dataframe with statistics of maxima in each TWD phase.

Examples

```
library(dendRoAnalyst)
data(gf_nepa17)
df1=gf_nepa17[2500:3500,]
twd_max<-twd.maxima(df=df1, TreeNum=2, showPlot=FALSE)
head(twd_max,10)
```

Index

* datasets

- gf_nepa17, [6](#)
- ktm_rain17, [7](#)
- nepa, [8](#)
- nepa17, [8](#)
- nepa2, [9](#)

clim.twd, [2](#)

daily.data, [3](#)

dendro.resample, [3](#), [4](#)

dendro.truncate, [5](#)

gf_nepa17, [6](#)

jump.locator, [6](#)

ktm_rain17, [7](#)

na.spline, [14](#)

nepa, [8](#)

nepa17, [8](#)

nepa2, [9](#)

network.interpolation, [9](#)

phase.sc, [10](#)

phase.zg, [12](#), [15](#)

polygon, [13](#)

smooth.Pspline, [11](#)

spline.interpolation, [14](#)

twd.maxima, [15](#)